

# SPICY

**HIGH-PROTECTION, STYLISH AND COLOURFUL DESIGN!**

Bollé Safety eyewear is ideal for a variety of applications from construction sites through to industry. Our latest innovation is a range of safety glasses with prescription lenses in stylish, colourful frames. KICK and SPICY come in two unisex models, one with impact-resistant side shields for use in industry and the other with robust design for the office.

★ **EXCELLENCE**  
A concentrate of innovation  
for greater comfort,  
performance and style



SPISLTO



SPISBKGN



SPIMBKB



29 g

**SUPPLIED WITH**

Hard case,  
microfibre cloth,  
cord



**FRAME**

• TRNZZ/TPR

**LENS MATERIAL AVAILABLE**







• CR39  
• Polycarbonate

- + **BUILT-IN SIDE SHIELDS**
- + **EN166 LOW ENERGY IMPACT RESISTANCE - F MARKING**
- + **CHOICE OF 3 COLOURS - UNISEX**
- + **AVAILABLE WITH ALL TYPES OF LENSES**
- + **AVAILABLE WITH ALL THE COATINGS IN THE EXCELLENCE PRESCRIPTION RANGE**

**bollé**  
SAFETY

# SPICY

**HIGH-PROTECTION, STYLISH AND COLOURFUL DESIGN!**

MODEL	REFERENCES	VERSIONS	SIZE	FRAME MARKING	TEMPLE LENGTH
SPICY	SPISLTO	 Light brown tortoise	53/19	 EN166 F CE	138 mm
	SPISBKGN	 Black/green	53/19	 EN166 F CE	138 mm
	SPIMBKB	 Black/blue	53/19	 EN166 F CE	138 mm

## LENS MARKING

### Polycarbonate lens:

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

### CR39 lens:

**S.** Extra strong, resists a 22 mm 43 g ball falling 1.30 m at 5,1 m/s.

## FRAME MARKING

**EN 166** : guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

**CE** European standard  Manufacturer name

**Bollé safety product approval certificates to CE standards will be sent on request.**

## STANDARD ASSEMBLY RESTRICTIONS:

**Maximum sphere power:** +10/-10

**Maximum cylinder compared with sphere :** +/-6.

## CORRECTED BASE:

**Corrected base :** 4

## CLEANING AND STORAGE

**CLEANING** : The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE** : Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE** : All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE			
	SPISLTO	SPISBKGN	SPIMBKB
Per piece	3660740009069	3660740009052	3660740009045

CHARACTERISTICS	
LENS	CR39, Polycarbonate
TYPES OF CORRECTIONS AVAILABLE	Single vision - Bifocal - Progressive - Free form - Degressive
FRAME	PC/TPR



31/08/2018

Europe Bollé Safety  
34 rue de la Soie  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

**bolle-safety.com**

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

**bolle**  
SAFETY